

Safety Data Sheet

Per GHS Standard Format

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: California DecoTurf® II No. 63075

Recommended Use of Product: Rubberized Coating for Resilient Athletic Surfacing

Information on the Supplier of the Safety Data Sheet

Manufacturer's Name:
California Products Corporation
150 Dascomb Road
Andover, MA 01810
P: 978-623-9980 F: 978-623-9960

Emergency Telephone Numbers:
CHEM TEL: (U.S.): 1-800-255-3924
(Outside the U.S.): 813-248-0585

SECTION 2: HAZARDS IDENTIFICATION

Signal Word: **DANGER**



GHS Label Statements

Hazard Statements:
May be harmful if swallowed
Can cause mild skin irritation
Can cause eye irritation on contact
May cause respiratory irritation
May cause cancer

Classification

This product is considered hazardous by
The 2012 OSHA Hazard Communication Standard
(29 CFR 1910.1200)
Acute Toxicity-Inhalation (Vapors) Category 4
Acute Toxicity-Inhalation (Dust-mists) Category 4
Serious eye damage/eye irritation – Category 2
Skin sensitization – Category 1
Carcinogenicity – Category 2

PRECAUTIONARY STATEMENTS

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection (eye protection, gloves) during application. When grinding/sanding dry films, wear respiratory protection.

Response: If on skin, wash with plenty of soap and water. If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If inhaled, remove victim to fresh air. If exposed or concerned, get medical advice.

Storage: Keep closures tight and containers upright to prevent leakage. **KEEP FROM FREEZING.**
Product is non-combustible.

Disposal: The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

Hazards Not Otherwise Classified (NHOC): Not applicable

Other Information: Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.

SECTION 3: COMPOSITION INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>CAS No.</u>	<u>Weight, %</u>
Ethylene glycol	107-21-1	1-5
Crystalline silica	14808-60-7	2-8

Note: Also contains 20-25% non-hazardous cured black EPDM rubber

SECTION 4: FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye Contact

If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

Skin Contact

Wash skin with soap and water. In the case of skin irritation or allergic reactions see a physician. May cause an allergic skin reaction.

Inhalation

Remove to fresh air. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately. If not breathing, give artificial respiration. Do not breathe dust.

Ingestion

Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid breathing vapors or mists.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

Burning sensation. Coughing and/or wheezing. Difficulty in breathing. Itching. Rashes. Hives.

Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically. May cause sensitization of susceptible persons.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Product is/or contains a sensitizer. May cause sensitization by skin contact.

Uniform Fire Code Sensitizer: Liquid Toxic: Liquid

Hazardous Combustion Products

Carbon oxides

Explosion Data

Sensitivity to mechanical impact No.

Sensitivity to static impact No.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Ensure adequate ventilation. Avoid breathing vapors or mists. Avoid generation of dust.

Other Information

Refer to protective measures listed in Sections 7 & 8

Environmental Precautions

Environmental Precautions

Refer to protective measures listed in Sections 7 & 8.

Methods and Material for Containment and Cleaning Up**Methods for Containment**

Prevent further leakage or spillage if safe to do so

Methods for Cleaning Up

Immediately place absorbent material in a sealed water-filled metal container to avoid spontaneous combustion of absorbent material contaminated with this product. Pick up and transfer to properly labeled containers.

SECTION 7: HANDLING AND STORAGE**Precautions for Safe Handling****Handling**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Avoid breathing vapors or mists. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash before reuse. Keep away from contact with clothing and other combustible materials to avoid fire.

Conditions for Safe Storage, Including any Incompatibilities**Storage**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children.

Incompatible Products

None known based on information supplied

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylene glycol 107-21-1	TWA: 50 ppm	TWA: 50 ppm (STEL 100 mg/m ³)	---
Crystalline silica 14808-60-7	TWA: 0.1 mg/m ³ (respirable dust)	0.1 mg/m ³ (respirable dust)	---
Chrome III oxide	TWA 0.5 mg/m ³	TWA 0.5 mg/m ³	---
Iron oxide 1309-37-1	TWA 5mg/m ³	10 mg/m ³	---

ACGIH TLV: American Conference of Governmental Industrial Hygienists – Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration – Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters

Appropriate Engineering Controls**Engineering Measures**

Showers / Eyewash Stations / Ventilation Systems

Individual Protection Measures, such as Personal Protective Equipment**Eye/Face Protection**

If splashes are likely to occur, wear safety glasses with side shields (or goggles). None required for consumer use.

Skin and body Protection

Wear protective gloves and protective clothing

Respiratory Protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**Physical State:** Viscous liquid**Odor:**

Very Slight

Appearance: Milky**Odor Threshold:**

No information available

Color: No information available

<u>Property</u>	<u>Values</u>	<u>Remarks/Method</u>
pH	8.5	None known
Melting/freezing point	No data available	None known
Boiling point/boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		
Upper flammability limit	No data available	None known
Lower flammability limit	No data available	None known
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Miscible in water	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Explosive properties	No data available	None known
Oxidizing properties	No data available	None known

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle size	No data available
Particle size distribution	No data available

SECTION 10: STABILITY AND REACTIVITY

Reactivity

No data available

Conditions to Avoid

Excessive heat

Chemical Stability

Stable under recommended storage conditions

Incompatible Materials

None known based on information supplied

Possibility of Hazardous Reactions

None under normal processing

Hazardous Decomposition Products

Carbon oxides

Hazardous Polymerization

Hazardous polymerization does not occur

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Product Information

Product does not present an acute toxicity hazard based on known or supplied information

Inhalation

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation (based on components).

Eye Contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. May cause redness, itching, and pain. May cause temporary eye irritation.

Skin Contact

Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene Glycol 107-21-1	= 4700 mg/kg (Rat)		< 200 mg/m ³ (Rat) 4 hr
Crystalline silica 14808-60-7	> 3360 mg/kg (Mouse)		> 5000 mg/kg (Rat) 4 hr

Information on Toxicological Effects**Symptoms**

May cause redness and tearing of the eyes, coughing and/or wheezing, itching, rashes and hives.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure**Sensitization**

May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects

No information available

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Crystalline silica 14808-60-7	X			X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 – Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B – Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X-Present

Reproductive Toxicity, STOT Single Exposure, STOT Repeated Exposure:

No information available

Chronic Toxicity

Titanium dioxide has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B) by inhalation. Contains a known or suspected carcinogen.

Target Organ Effects

Eyes, respiratory system, skin, gastrointestinal tract (GI) & lungs.

Aspiration Hazard

No information available

Numerical Measures of Toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 8,711.00 mg/kg	ATEmix (inhalation-dust/mist) 2.41 mg/l
ATEmix (dermal) 21,608.00 mg/kg (ATE)	ATEmix (inhalation-vapor) 16.00 ATEmix
ATEmix (inhalation-gas) 3,118.00 ppm (4hr)	

SECTION 12: ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life.

<i>Chemical Name</i>	<i>Toxicity to Algae</i>	<i>Toxicity to Fish</i>	<i>Toxicity to Microorganisms</i>	<i>Daphnia Magna (Water Flea)</i>
Ethylene Glycol 107-21-1	(Chlorella pyrenoidosa) 180,000 mg/L toxic Toxicity Threshold (cell multiplication Inhibition test): Algae (Microcystis acruginosa), 2000 mg/L; Green algae	LC50: = 41000 mg/L 96h [Fish (Trout)] 96h [Fish (bluegill fish)] 34250 mg/L 72h [Fish (Goldfish)]	No data available	46300 mg/L 48h (water flea)

Persistence and Degradability

No information available

Bioaccumulation

<i>Chemical Name</i>	<i>Log Pow</i>
Ethylene glycol 107-21-1	No information available

Other Adverse Effects

No information available

SECTION 13: DISPOSAL CONSIDERATIONS**Waste Treatment Methods****Disposal Methods**

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations

California Hazardous Waste Codes

331

SECTION 14: TRANSPORT INFORMATION

<u>DOT</u>	Not Regulated
Proper Shipping Name	Non-Regulated
Hazard Class	N/A

TDG
No data available

IATA
No data available

IMDG/IMO
No data available

SECTION 15: REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL

TSCA – United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL – Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains no chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

<i>Chemical Name</i>	<i>California Proposition 65</i>
Ethylene glycol – 107-21-1	Reproductive toxicant
Crystalline silica – 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

<i>Chemical Name</i>	<i>New Jersey</i>	<i>Massachusetts</i>	<i>Pennsylvania</i>	<i>Rhode Island</i>	<i>Illinois</i>
Ethylene glycol – 107-21-1	X	X	X	X	
Crystalline silica – 14808-60-7	X	X	X		

International Regulations

Canada
 WHMIS Hazard Class
 D2A – Very toxic materials
 D2B – Toxic materials



SECTION 16: OTHER INFORMATION

NFPA	Health Hazards 2	Flammability 0	Instability 0	Physical and Chemical Hazards
HMIS	Health Hazards 2*	Flammability 0	Physical Hazard 0	Personal Protection
				X

Chronic Hazard Star Legend * = Chronic Health Hazard

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD (5323) or log on to: www.epa.gov/lead